



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: PS7224-20HW

### 24-outlet Vertical Power Strip with Hardwire Input and 20A Circuit Breaker

#### Highlights

- AC input hardwired via knockout on unit
- 24 outlets
- Ideal for applications requiring permanent installation



#### Description

Tripp Lite's PS7224-20HW Power Strip offers 20 amp multi-outlet AC power distribution in a convenient 72 inch hardwire cabinet. Includes knockout panels to accept 3/4 in. conduit fittings for hardwire installation and 24 output receptacles with 2.795 inch center-to-center spacing. Ideal for horizontal or vertical raceway style power distribution in office, workbench, industrial, networking and telecom applications.

INPUT/OUTPUT: Input: Hard-wire access via knockout panels that accept 3/4 inch conduit fittings

Output: 24 outlets total, 2 NEMA 5-15/20R (20A) and 22 NEMA 5-15R (15A)

ELECTRICAL: 120V AC, 50/60Hz, 20A (no circuit breaker)

FORMAT: 72 inch strip format with 24 outlets

#### Applications

- Offers multiple outlet power distribution for a variety of applications, including office, workbench, industrial, networking, telecom and more.

#### Package Includes

- PS7224-20HW
- Instruction manual

#### Features

- Versatile all-metal 72 inch format with outlets arranged in a single row
- Knockout panels for 3/4 inch conduit fittings allow permanent hardwire installation
- Ideal for horizontal or vertical raceway style power distribution in office, workbench, industrial, networking and telecom applications
- 24 outlets total, 2 NEMA 5-15/20R (20A) and 22 NEMA 5-15R (15A)
- 20 amp electrical capacity
- 120V AC, 50/60Hz electrical compatibility

#### Specifications

<b>OUTPUT</b>
---------------

<b>Frequency compatibility</b>	50 / 60 Hz
<b>Output watts</b>	2400
<b>Circuit Breaker (amps)</b>	20
<b>Outlet quantity / type</b>	22 NEMA 5-15R & 2 NEMA 5-15/20R
<b>Outlet spacing</b>	2.795 in.
<b>INPUT</b>	
<b>Nominal Input Voltage(s) Supported</b>	120V AC
<b>Recommended Electrical Service</b>	20A 120V
<b>Input connection type</b>	Hardwire
<b>Voltage compatibility (VAC)</b>	120
<b>PHYSICAL</b>	
<b>Unit Dimensions (HWD/in)</b>	72 x 1.5 x 1.5
<b>Unit Dimensions (HWD/cm)</b>	182.88 x 3.8 x 3.8
<b>Material of construction</b>	Metal
<b>Integrated keyhole mounting tabs</b>	Mount through housing supports bolt down installation to a variety of flat surfaces
<b>Receptacle Color</b>	Almond
<b>Outlets center to center measurement</b>	101.60mm
<b>CERTIFICATIONS</b>	
<b>cUL / CSA (Canada)</b>	cUL
<b>Approvals</b>	UL
<b>WARRANTY</b>	
<b>Product Warranty Period (Worldwide)</b>	Lifetime limited warranty

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?variables.txtModelID=201](http://www.tripplite.com/en/products/model.cfm?variables.txtModelID=201).

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.